

## PANASONIC BL-C10A



Server	
<b>Image data compression system</b>	JPEG (Motion JPEG for moving image display)
<b>Video resolution</b>	640 x 480, 320 x 240, 160 x 120
<b>Image quality</b>	3 modes (favor clarity, standard, favor motion)
<b>Frame rate*<sup>1</sup></b>	Max. 7.5 frames/sec (640 x 480) Max. 15 frames/sec (320 x 240) Max. 15 frames/sec (160 x 120)
<b>Security</b>	User ID/Password
<b>Supported protocols</b>	TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, DNS, ARP, ICMP, POP3, NTP, DDNS
<b>User access limit</b>	Max. 20 simultaneous accesses
<b>Buffered images*<sup>2</sup></b>	Approx. 250 images (320 x 240) · standard image quality
Network camera	

<b>Zoom</b>	10 x digital zoom (by area)
<b>Viewing angle</b>	43° horizontal (total 143°) 32° vertical (total 82°)
<b>Pan (horizontal direction)</b>	-50° up to +50°
<b>Tilt (vertical direction)</b>	-40° up to +10°
<b>Revolving speed</b>	Pan: Max. 50°/sec Tilt: Max. 50°/sec
<b>Number of pixels</b>	1/4-inch, approx. 320,000 pixels, CMOS sensor
<b>Lens focal point</b>	Fixed (focal range: 0.5 m to ∞)
<b>Lens brightness</b>	F2.8
<b>Required light intensity</b>	1 to 10,000 lux
<b>Terminal</b>	
<b>Network interface</b>	Ethernet (10Base-T/100Base-TX)
<b>General</b>	
<b>Operating temperature</b>	41°F to 104°F (+5°C to +40°C)
<b>Operating humidity</b>	20% to 80% (No condensation)
<b>Dimensions (H x W x D)</b>	3 7/8 x 2 15/16 x 2 3/8 inches (98 x74 x61 mm)
<b>Weight (Only the unit)</b>	0.37 lb (170 g)
<b>Power supply</b>	AC adaptor: Input 120 V AC(USA), 100-240 V AC(Others), Output 9 V DC
<b>Consumption</b>	3.5 W