

PANASONIC BL-C20A



Server	
Image data compression system	JPEG (Motion JPEG for moving image display)
Video resolution	640 x 480, 320 x 240, 160 x 120
Image quality	3 modes (favor clarity, standard, favor motion)
Frame rate ^{*1}	Max. 7.5 frames/sec (640 x 480) Max. 15 frames/sec (320 x 240) Max. 15 frames/sec (160 x 120)
Security	User ID/Password
Supported protocols	TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, DNS, ARP, ICMP, POP3, NTP, UPnP
User access limit	Max. 20 simultaneous accesses
Buffered images ^{*2}	Approx. 250 images (320 x 240), · standard image quality
Network camera	
Zoom	10 x digital zoom (by area)

Viewing angle	53° horizontal 41° vertical
Number of pixels	1/4-inch, approx. 320,000 pixels, CMOS sensor
Lens focal point	Fixed (focal range: 0.3 m to ∞)
Lens brightness	F2.8
Required light intensity	10 to 10,000 lux (in Color Night View Mode : 4 to 10,000 lux)
Wireless	
Standards	802.11 b/g
Antenna	Diversity
Number of channels	11 ch. (USA), 13ch. (Others)
Transmission speed	up to 54 Mbps.
Security	WEP 64/128/152 bit
Terminal	
Network interface	Ethernet (10Base-T/100Base-TX)
General	
Operating temperature	41°F to 104°F (+5°C to +40°C)
Operating humidity	20% to 80% (No condensation)
Dimensions (H x W x D)	3 3/8 x 3 3/8 x 1 3/8 inches (85 x85 x35.5 mm)
Weight (Only the unit)	0.36 lb (165 g)
Power supply	AC adaptor: Input 120 V AC(USA), 100-240 V AC(Others), Output 9 V DC
Consumption	4.6 W