

PANASONIC BL-C30A



| Server | |
|--------------------------------------|---|
| Image data compression system | JPEG (Motion JPEG for moving image display) |
| Video resolution | 640 x 480, 320 x 240, 160 x 120 |
| Image quality | 3 modes (favor clarity, standard, favor motion) |
| Frame rate^{*1} | Max. 7.5 frames/sec (640 x 480) Max. 15 frames/sec (320 x 240) Max. 15 frames/sec (160 x 120) |
| Security | User ID/Password |
| Supported protocols | TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, DNS, ARP, ICMP, POP3, NTP, DDNS |
| User access limit | Max. 20 simultaneous accesses |
| Buffered images^{*2} | Approx. 250 images (320 x 240) · standard image quality |
| Network camera | |
| Zoom | 10 x digital zoom (by area) |
| Viewing angle | 43° horizontal (total 143°) 32° vertical (total 82°) |

| | |
|-----------------------------------|--|
| Pan (horizontal direction) | -50° up to +50° |
| Tilt (vertical direction) | -40° up to +10° |
| Revolving speed | Pan: Max. 50°/sec Tilt: Max. 50°/sec |
| Number of pixels | 1/4-inch, approx. 320,000 pixels, CMOS sensor |
| Lens focal point | Fixed (focal range: 0.5 m to ∞) |
| Lens brightness | F2.8 |
| Required light intensity | 1 to 10,000 lux |
| Wireless | |
| Standards | 802.11 b/g |
| Antenna | Diversity |
| Number of channels | 11 ch. (USA), 13ch. (Others) |
| Transmission speed | up to 54 Mbps. |
| Security | WEP 64/128/152 bit |
| Terminal | |
| Network interface | Ethernet (10Base-T/100Base-TX) |
| General | |
| Operating temperature | 41°F to 104°F (+5°C to +40°C) |
| Operating humidity | 20% to 80% (No condensation) |
| Dimensions (H x W x D) | 3 7/8 x 2 15/16 x 2 7/8 inches (98 x74 x73 mm) |
| Weight (Only the unit) | 0.44 lb (200 g) |
| Power supply | AC adaptor: Input 120 V AC(Canada), 100-240 V AC(Others), Output 12 V |

| | |
|--------------------|-------|
| | DC |
| Consumption | 6.4 W |